

## SOMAFIX COMBI POLYURETHANE FOAM 2 IN 1 GUN & STANDARD VALVE

Technical Data Sheet Date of issue: 21/03/2017 Rev

Revision date: 30/06/2017

017 Version: 0.1

n: 0.1 TDS No.: TDS.09.14

 1. Product Description

 Product description
 : SOMAFIX COMBI POLYURETHANE FOAM 2in1 GUN & STANDARD VALVE PU FOAM is a single component PU foam used both with gun and the straw adapter. The valve system allows working with gun and straw whenever needed.

 Use of the substance/mixture
 : Polyurethane Foam

 Recommended use
 : Industrial use Professional uses Consumer use

 2. Characteristics
 : Yields higher volume gun and standard straw applications

Easier and reusability gun and standard straw applications

Resistant to every kind of weather conditions, seawater, steam and moisture

### 3. Application

- Fixing doors, windows and similar frames
- Using in insulation of hot and cold water pipes and electrical equipments
- Filling up the gaps, holes and cracks
- Bonding to all kinds of building materials except silicone, teflon, polyethylene and polypropylene

### 4. Application Instructions

- Application temperature is between 0 °C to +35 °C
- Shake the can strongly for 30 seconds
- Install the foam gun or straw on the can
- Remove the dirt, dust and grease from the application place
- Turn the can upside down and press trigger
- Moisturising accelerates reaction and ensures a productive result
- Fresh foam residue can be cleaned by using PU FOAM CLEANER
- Cured Foam can be cleaned mechanically
- Can be shaved, sandpapered and painted after it get hardens in 1 or 3 hours

### 5. Technical Specifications (@ 23 °C 50% RH)

Colour	: light yellow
Odour	: characteristic
Curing System	: Moisture
Skin Forming Time (FEICA TM1014)	: 8 - 10 minutes
Cutting Time (FEICA TM1005)	: 35-45 minutes (For Gun); 45-60 minutes (For Straw)
Ultimate Elongation (DIN 53504)	: 19 %
Tensile Strength (DIN 53504)	: 3 N/cm <sup>2</sup>
Density	: 17 - 20 g/cm³
Flash point	: Not applicable, as aerosol.(≤ 50°C)
Thermal Resistance	: -40 - 100 °C
Yield (FEICA TM1003)	: 50-55 I (For Gun) / 45-50 I (For Straw)
Closed Cell Content	: 70-80 % (For Gun) / 60-70 % (For Straw)
Thermal Conductivity	: 25 - 30 mW/min.K
Application Temperature	: 0 - 35 °C

SOMA KİMYA SANAYİ VE TİCARET A.Ş.



# SOMAFIX COMBI POLYURETHANE FOAM 2 IN 1 GUN & STANDARD VALVE

**Technical Data Sheet** Date of issue: 21/03/2017

Revision date: 30/06/2017

Version: 0.1

TDS No.: TDS.09.14

Soma Kimya uses test methods approved by FEICA designed to deliver transparent and reproducible test results, ensuring customers have an accurate representation of product performance. FEICA OCF test methods are available at: http://www.feica.com/our-industry/pu-foam-technology-ocf . FEICA is a multinational association representing the European adhesive and sealant industry, including one-component foam manufacturers. Further information at: www.feica.eu

6. Packaging				
Packaging	:	Aerosol.		
Canister 750 ml		Package 12 pcs/ctn		
7. Shelf Life and Storage				
	$\sim$ Distant from sumlimit. Do not suppose to temperatures supposition 50 °C / 400 °C. Stars locked			
Storage conditions	·	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.		
Storage temperature	:	: 0 - 30 °C		
Canister 750 ml		18 mor	ths (after production date if stored at room temperature)	
8. Health and Safety				
Adverse physicochemical, human health and environmental effects	:	Pressurised container: May burst if heated,Extremely flammable aerosol,Suspected of causing cancer,May cause damage to organs through prolonged or repeated exposure,Harmful if inhaled,May cause respiratory irritation,Causes skin irritation,May cause an allergic skin reaction,Causes serious eye irritation,May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
First-aid measures general	:	IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.		
First-aid measures after inhalation	:	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.		
First-aid measures after skin contact	:	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.		
First-aid measures after eye contact	:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
First-aid measures after ingestion	:	Call a poison center or a doctor if you feel unwell.		
Symptoms/effects after inhalation	:	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
Symptoms/effects after skin contact	:	Irritation. May cause an allergic skin reaction.		
Symptoms/effects after eye contact	:	Eye irritation.		
Other medical advice or treatment	:	Treat symptomatically.		
Hand protection	:	Protective gloves		
Eye protection	:	Safety glasses		
Skin and body protection	:	Wear suitable protective clothing		
Respiratory protection	:	[In case of inadequate ventilation] wear respiratory protection.		

### 9. Remarks

Remarks

: For further information, please refer to the Safety Data Sheet

### 10. Standards and Certificates

No information available

#### **Technical Data Sheet**

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product