

# **SOMAFIX INSULATION SPRAY FOAM**

# **Technical Data Sheet**

Issue date: 30/11/2020 Revision date: 31/10/2022 Version: 1.2 TDS No.: TDS.09.73

#### 1. Product Description

Product description : SOMAFIX INSULATION SPRAY FOAM is a one component polyurethane foam which has

effective thermal and sound insulation properties.

Product form : Mixture

Trade name : INSULATION SPRAY FOAM

Use of the substance/mixture : Polyurethane Foam

Recommended use : Industrial use

Professional uses Consumer use

Type of product : Aerosol
Vaporizer : Aerosol

## 2. Characteristics

Characteristics : Carries excellent adhesion power to all kinds of materials.

Applied easily and efficiently with its special applicator nozzle.

When applied in 2 cm thickness, provides insulation up to 2 m2 with 1 can.

### 3. Application

• Used for insulation of walls, doors, pipes, roofs, attics, ceilings, floors, tanks etc.

# 4. Application Instructions

- Shake the can strongly for 30 seconds
- Install the foam gun on the can
- Place the special applicator nozzle provided with each can to the tip of the gun.
- Adjust the nozzle to get desired application positions.
- · Make sure the surface to be applied is dry and clean, free of dust and grease
- For best results, the surface should be moisturized before the application.
- Apply by spraying from a 30-40 cm distance.
- If desired, extra layers can be applied 30 minutes after the first layer.
- After the application, any foam residue on the gun, valve and the surface should be cleaned with SOMAFIX POLYURETHANE FOAM & GUN CLEANER.
- Application Tempereature: +5°C to +30°C. Ideal can temperature: 20°C.

# 5. Technical Specifications (@ 23 °C 50% RH)

Physical state: LiquidAppearance: Aerosol.Colour: light yellowOdour: characteristicCuring System: Moisture

Skin Forming Time (FEICA TM1014) : 5-10 minutes @23°C Cutting Time (FEICA TM1005) : > 60 minutes @23°C

Density :  $17 - 20 \text{ g/cm}^3$ Thermal Resistance : -40 - 100 °C

Yield (FEICA TM1003) : 2 m² When applied in 2 cm thickness

Thermal Conductivity : 0.038 W/m.K

Fire Class (DIN 4102) : B3

Application Temperature :  $0 \rightarrow 35$  °C



# SOMAFIX INSULATION SPRAY FOAM

# Technical Data Sheet

Issue date: 30/11/2020 Revision date: 31/10/2022 TDS No.: TDS.09.73 Version: 1.2

Soma Kimya uses test methods approved by FEICA designed to deliver transparent and reproducible test results, ensuring customers have an accurate representation of product performance. FEICA OCF test methods are available at: http://www.feica.com/our-industry/pu-foam-technology-ocf . FEICA is a multinational association representing the European adhesive and sealant industry, including one-component foam manufacturers. Further information at: www.feica.eu

### 6. Packaging

**Packaging** : Aerosol.

| Canister 850 ml | Package 12 pcs/box |
|-----------------|--------------------|
|-----------------|--------------------|

### 7. Shelf Life and Storage

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Storage temperature  $5 \rightarrow 30 \, ^{\circ}\text{C}$ 

Canister 850 ml 15 months (after production date if stored at room temperature.)

# 8. Health and Safety

Adverse physicochemical, human health and

environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Harmful if swallowed. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

First-aid measures general

IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you

feel unwell.

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Call a poison center or a

doctor if you feel unwell.

First-aid measures after skin contact

Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

Rinse mouth. Call a poison center or a doctor if you feel unwell.

Symptoms/effects after inhalation

May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

Symptoms/effects after skin contact

: Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact

: Eye irritation.

Other medical advice or treatment

: Treat symptomatically.

Hand protection

Protective gloves

Eye protection

Safety glasses

Skin and body protection

: Wear suitable protective clothing

Respiratory protection

: [In case of inadequate ventilation] wear respiratory protection.

### 9. Remarks

No information available

### 10. Standards and Certificates

No information available

Technical Data Sheet

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, v do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in an other product, this SDS information may not be applicable