

### 1. Product Description

Product description	: SOMAFIX SILICONE LUBRICANT SPRAY provides dry lubrication, minimizes static electric, prevents material from adhering and protects against rust and static electric. It does not adhere, give stains or oxidize
Use of the substance/mixture	: Silicone Lubricant Spray
Recommended use	: Industrial use Professional uses Consumer use

### 2. Characteristics

Characteristics	: Repels water and humidity, prevents jamming and delivers waterproofing Prevents corrosion of hard and soft material with each other Not adheres, gives stains or oxidizes
-----------------	---

### 3. Application

- Using against jamming and chilling at all kinds of metal, plastic, wooden, rubber derivative materials, ignition mechanisms of electrical systems of vehicles, doors, windows and slide doors

### 4. Application Instructions

- Application temperature is between +5 °C to +35 °C
- Shake well the container and spray on the parts to be lubricated with silicon by holding the tube 15-20 cm away vertically

### 5. Technical Specifications (@ 23 °C 50% RH)

Basis	: Solvent mixture.
Odour	: Characteristic
Flash point	: Not applicable, as aerosol.(≤ 50°C)
Application Temperature	: 5 - 35 °C

### 6. Packaging

Packaging	: Aerosol.
-----------	------------

Canister 400 ml	Package 12 pcs/ctn
-----------------	--------------------

### 7. Shelf Life and Storage

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: -10 - 35 °C

Canister 400 ml	36 months (after production date if stored at room temperature.)
-----------------	--

### 8. Health and Safety

Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated,Extremely flammable aerosol,Suspected of causing cancer,Suspected of damaging fertility or the unborn child,May cause damage to organs through prolonged or repeated exposure,May cause drowsiness or dizziness,Causes skin irritation,May be fatal if swallowed and enters airways,Toxic to aquatic life with long lasting effects.
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.
Other medical advice or treatment	: Treat symptomatically.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.

### 9. Remarks

Remarks : For further information, please refer to the Safety Data Sheet

### 10. Standards and Certificates

No information available

Technical Data Sheet

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*